

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : G21C 7/113	A1	(11) International Publication Number: WO 00/39808 (43) International Publication Date: 6 July 2000 (06.07.00)
<p>(21) International Application Number: PCT/SE99/02268</p> <p>(22) International Filing Date: 6 December 1999 (06.12.99)</p> <p>(30) Priority Data: 9804518-0 23 December 1998 (23.12.98) SE</p> <p>(71) Applicant (for all designated States except US): ABB ATOM AB [SE/SE]; S-721 63 Västerås (SE).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): BERNANDER, Örjan [SE/SE]; Eldstensgatan 6, S-723 53 Västerås (SE). HELMERSSON, Sture [SE/SE]; Strandvägen 2, S-730 40 Kolbäck (SE).</p> <p>(74) Agent: ABB AB; Patent, Gideonsbergsgatan 2, S-721 78 Västerås (SE).</p>	<p>(81) Designated States: JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments. In English translation (filed in Swedish).</i></p>	

(54) Title: CONTROL ROD

(57) Abstract

A control rod (2) for boiling water reactor comprising four absorber blades (6, 7, 8, 9) which form an orthogonal cross with a cruciform centre (10). The width of the absorber blades coincides with the radial direction of the control rod and the length of the absorber blades coincides with the axial direction of the control rod. Each one of the absorber blades comprises an absorber material distributed in the longitudinal direction, whereby a mean value of the quantity of absorber material per unit of length of the control rod is smaller in the upper part of the control rod than in the lower part thereof. Each one of the absorber blades comprises in its upper part (15) an inner part arranged radially inside an outer part, where the outer part is provided with absorber material whereas the inner part lacks absorber material, whereby said inner part in at least some portion constitutes at least one-fourth of the width of the absorber blade.

